

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (Currently Amended) A method of connecting to a radiocommunication network a terminal which is in a standby mode because of temporary unavailability of a signal from the network, said method comprising periodically scanning frequencies of said radiocommunication network, only when signal intensity was approximately constant before said standby, using one or more sequences each associated with a predetermined list of frequencies from all said frequencies.

2. (Original) The method claimed in claim 1 wherein said list of frequencies associated with each sequence does not vary.

3. (Original) The method claimed in claim 1 wherein said list of frequencies associated with each sequence varies.

4. (Previously Presented) The method claimed in claim 1 further comprising storing the last frequencies available before disconnection from the network so that the first scanning sequence scans said last available frequencies.

5. (Previously Presented) The method claimed in claim 4 further comprising measuring the intensity of the last available frequencies of the signal before disconnection from the network.

6. (Original) The method claimed in claim 5 wherein the frequency scanning is partial only if the intensity of the last frequencies available exceeds a predetermined threshold value.

7. (Previously Presented) The method claimed in claim 5 further comprising determining the number of last frequencies available before disconnection from the network carrying a signal of intensity greater than a predetermined threshold value.

8. (Original) The method claimed in claim 7 wherein the frequency scanning is partial only if said number of last frequencies available carrying a signal of intensity greater than a predetermined threshold intensity is itself greater than a given number.

9. (Previously Presented) A terminal adapted to be connected to one or more radiocommunication networks operating on different frequencies, said terminal comprising:  
  
means for determining what type of scanning to perform based on signal intensity; and

means for partially scanning the frequencies of the network using one or more sequences each of which is associated with a predetermined list of frequencies selected from all said frequencies.

10. (Previously Presented) The terminal claimed in claim 9, further comprising means for selecting partial or complete scanning of the various frequencies.

11. (Previously Presented) The terminal claimed in claim 9, wherein said means for determining what type of scanning to perform is further based on whether the intensity of the signal before standby was constant.

12. (Previously Presented) The terminal claimed in claim 11, wherein when said intensity of the signal before the standby is constant, partial scanning means perform scanning using one or more sequences each of which is associated with a predetermined list of frequencies selected from all said frequencies.

13. (Previously Presented) The terminal claimed in claim 12, further comprising means for scanning all said frequencies when the intensity of the signal before the standby was varying.

14. (Previously Presented) The method claimed in claim 1, wherein when the signal intensity was varying before the standby, scanning all the frequencies of the radiocommunication network.